



Item No.

8752 Soft Serve Freezer

Single Flavor, Pump

Features

Offer all the popular soft serve variations from low or non-fat ice creams to custards, yogurt and sorbet.

Freezing Cylinder

One, 3.4 quart (3.2 liter).

Refrigerated Mix Storage Cabinet

Lower front mix cabinet is independently refrigerated to maintain mix below 41°F (5°C). Door is hinged on the right. One, 15 gallon (57.0 liter) mix tank. Air/ mix pump delivers the precise amount of air and mix to the freezing cylinder.

Indicator Lights

Mix Low light alerts the operator to add mix. Audible alarm may be enabled to sound when mix is low. When the Mix Out light flashes, the unit shuts down automatically to prevent damage.

Electronic Controls

Finished product quality is monitored by $\mathsf{Softech}^\mathsf{TM}$ controls that measure viscosity.

Standby

During long no-use periods, the standby feature maintains safe product temperatures in the mix hopper and freezing cylinder.

Two Locking Casters

Front casters have a locking feature for operators to lock to maintain equipment in place. The locking casters can be released to move the equipment for cleaning


Door Interlock System

Protects the operator from injury as the beater will not operate without the dispensing door in place.

750 N. Blackhawk Blvd. Rockton, Illinois 61072 800-255-0626 Phone 815-624-8333 Fax 815-624-8000 www.taylor-company.com info@taylor-company.com

ISO 9001:2015 Registered Firm





FIGURES IN BRACKETS INDICATE MILLIMETERS. DECIMAL DIMENSIONS EQUAL TO (PLUS OR MINUS 1/16 INCH [1.5mm]. * WATER COOLED ONLY

Weights	lbs.	kgs.	
Net	585	265.4	
Crated	594	269.4	
	cu. ft.	cu. m.	
Volume	72.2	2.04	
Dimensions	in.	mm.	
Width	26-9/16	5 519	
Depth	36	914	
Height	62-15/16	62-15/16 1599	
Floor Clearance	4-1/4	108	
I IUUI GIEdidIIGE	7 1/7	100	


*Mounted on standard casters

Electrical	Maximum Fuse Size	Minimum Circuit Ampacity	Poles (P) Wires (W)
208-230/60/1 Air	30	24	2P 3W
208-230/60/1 Water	30	23	2P 3W
208-230/60/3 Air	25	19	3P 4W
208-230/60/3 Water	25	19	3P 4W
220-240/50/1 Air	25	20	2P 3W
220-240/50/1 Water	25	20	2P 3W
220-240/50/3 Air	20	16	3P 4W
380-415/50/1 Water	12	11	4P 5W
380-415/50/3N~ Air	12	11	4P 5W

This unit may be manufactured in other electrical characteristics and may have additional regulatory agency approvals. Consult the local Taylor Distributor for other electrical characteristics and agency approvals based on specific electrical and country requirements.

(For exact electrical information and approval marks, always refer to the data label of the unit.) Continuing research results in steady improvements; therefore,

these specifications are subject to change without notice.



Authorized Taylor Distributor

Specifications

Electrical

One dedicated electrical connection is required. See the Electrical chart for the proper electrical requirements. Manufactured to be permanently connected. Consult your local Taylor distributor for cord & receptacle specifications as local codes allow.

Beater Motor

One, 1.5 HP.

Refrigeration System

One, 9,500 BTU/hr. R449A. Mix Cabinet Refrigeration, One, 800 BTU/hr. R134A. (BTUs may vary depending on compressor used.)

Air Cooled

Minimum 3" (76 mm) around all sides and 12" (305 mm) on top. Minimum air clearances must be met to assure adequate air flow for optimum performance.

Water Cooled

Water inlet and drain connections under side of base 3/8" FPT.

Options

- Cone Dispenser
- Draw Valve Lock Kit
- · Panel Spinner
- Sneeze Guard
- Syrup Rail Kit (side mount)

